

Composition

100% Super Fine Washable Wool (Super 120's)

キャラクター

オーストラリア産、エクストラファインメリノよりも細いスーパーファインメリノ(Super 120's)を100%使用の梳毛糸。17.5 μ に防縮加工を施しており手洗いが可能。細く長い繊維なので、チクチク感がなく着心地は満点、しなやかでソフトな風合い。発色が良く光沢感もあり、美しいシルエットの表現も可能としたハイグレードな素材。カラーは、深みのあるトップメランジと糸染めの展開。紡績、染めと全て国内工場生産しており、「MADE IN JAPAN」と言える糸。

特記事項

一部のトップ色（※）はバイオーダーになります。

ご使用時の注意点

- 品質の保持には十分努力しておりますが、生産ロット間の差異にはご注意をお願い致します。
- 編み組織や本数取り、色でも縮率は異なりますので、必ずテストをしてからのご使用をお願い致します。
- 工程の違いにより、メランジカラーとソリッドカラーでは風合いや縮率に差が発生することがあります。
- 当素材は染色工程上3%前後の目減りが発生することがあります。販売時には実費数量ではなく投入数量でのご請求となります。

ストックサービス

○ (2/60のみ)

ブックカラーミニマム

1kg

別注色

ソリッドのみ


別注色ミニマム

営業担当者にお問い合わせください。

適正ゲージ (参考)

2/60 18GG 1ply, 16GG 1ply, 12GG 2ply
3/60 16GG 1ply, 14GG 1ply

洗濯絵表示例



※洗濯表示につきましては、編み組織、デザイン、付属等を含めてご検討下さい。

Characteristics

Elegant washable wool yarn for high gauge.
Made from superfine Australian merino, it has an extremely soft texture.
Available in a wide range of stock service colours.

Special Instructions

The colors marked (※) are not stock service.

Notes

- Please note that the small differences of colour/texture/shrinkage between the production lots are inevitable.
- Please conduct enough trials in advance, as the final result depends greatly on the condition of knitting and washing.
- Due to the difference of production processes, the texture and the shrinkage may differ between solid colours and melange colours.
- Due to the dyeing method, the net weight of each cone may turn out lighter by about 3% after dyeing.

Stock Service

All colors are available for sampling.

Minimum Order Quantity

1 kg per colour

Your Own Colour

Solid Only

MOQ for your own colour

6 kg per colour

Dyeing Bath Lot

Top Dye (Melange)

Min: 200 kg
Max: 2000 (1 Lot)

Yarn Dye (Solid)

Min: 6 kg
Max: 100 kg (1 Lot)

Finishing

This is the instruction for finishing the product. For the care instructions, please refer to the labeling below.

- Washing at low-temperature water is recommended. Please steam press to set the shape before washing. After washing, please dry at low temperature.
- When ironing, please put a piece of cloth on the knitted panel. The temperature must be below 110°C.

Colour Fastness

Water at 37°C Grade 4

Light fastness Grade 4

Dry rubbing Grade 4

Wet rubbing Grade 4

Pilling Test

Grade 4

Suitable Gauge

2/60 18GG 1ply, 16GG 1ply, 12GG 2ply
3/60 16GG 1ply, 14GG 1ply

Labeling

